

Parameter	Value
Pixel Pitch	1.8mm - 2.571mm
LED Type	Full Black 3-in-1 SMD1515 - SMD2121
LED Configuration	1Red,1Green,1Blue
Brightness	1200cd/m ²
Module Size	W288mm×H216mm
Pixels Per Module	160×120 Dots - 112×84 Dots
Pixel Density	1440×240 Dots - 169,344 pixels/panel
Weight	35kg
Display Dimension	W576mm×H1944mm×D35mm
Maintenance	Front maintenance of module
Material	Aluminum
Environment	Indoor
Operating Temperature/Humidity	-10°C~+50°C/10~80%RH
Gap Between Modules	Seamless
Horizontal Viewing Angle	160°
Vertical Viewing Angle	160°
Color	4.4 Trillion
Contrast Ratio	3000:1
Input Power <Max>	600W
Input Power <Typical>	240W
Driving Method	Constant Current Drive
Video Frame Rate	50/60 Hz
Rate Refresh	≥3600 Hz
Input Voltage	100~240VAC
Input Power Frequency	50~60 Hz
Display Mode	Asynchronous / synchronous system
Signal Input	DVI/HDMI/VGA/SDI/DP/AV/S-Video, etc
Signal Output	HDMI
Connection Type	USB / Ethernet / WIFI / Internet
Supported Video Files	MPEG / H.264
LED Life Time	≥100,000 Hours
Standard Mounting Configuration	Side-mounted, Hanged
Professional Services	Design, configuration, install and service available

Note: Specifications are for reference only and are subject to change without notice.

